

# NUMERICAL SIMULATIONS OF NEUTRON TRANSPORT IN SPENT LWR FUEL ASSEMBLIES FOR BURN-UP CREDIT APPLICATION TECHNIQUES

★ Yasushi NAUCHI  
Takanori KAMEYAMA  
Akihiro SASAHARA

**CRIEPI**

*Central Research Institute of Electric Power Industry*

## Abstract

Numerical simulation of neutron transport in LWR FA are performed to develop confirmation methods of burn-up and reactivity depletion.



Principle results  
Neutron leakage probability  $P_L$  varies little with burn-up.  
  
The constant  $P_L$  is preferable for  
total neutron yield measurements (PWR & BWR)  
source multiplication method (PWR).

## Outline

- I. Introduction
- II. 3-D Nuclide Density Distribution
- III. Total Neutron yield (Passive)
- IV. Source Multiplication
- V. Conclusion and Future Work

## I. Introduction

- II. 3-D Nuclide Density Distribution
- III. Total Neutron yield (Passive)
- IV. Source Multiplication
- V. Conclusion and Future Work

## Requirement for Burn-up Credit for LWR Operation

- Spent fuel assemblies (FA) are discharged every cycle.  
*1/5~1/3 core equivalent*
- A discharged spent FA is stored in a rack in spent fuel pond (SFP) until radiation heat decays out.  
*capacity of SFP for storage is 4/3 core eq. in older PWR*
- Well cooled FAs must be shipped steadily.

To reduce the risk of shortage of the vacant racks,  
enhancement of **capacity** of **SFP** and **transport cask** is preferable.

For the enhancement, application of Burn-up credit (BUC) is effective.

## Burn-up Confirmation and Current Subject

For application of BUC for the transport,  
a confirmation measurement is required for every FA  
whether the declared burn-up / reactivity depletion of the FA  
based on **reactor record** is adequate.

Confirmation methods and devices had been developed.  
FORK, FORK+(US), PYTHON, NAJA(France), BUM(Japan), etc

However,  
current confirmation devices are calibrated utilizing postulated  
burn-up or nuclide density based on **reactor record**.

Errors originated in utilizing **reactor records** have been  
subtracted from the credit.

## Objective

To develop confirmation methods of burn-up and reactivity depletion of FA which dose not require the **reactor record** data for **calibration** in order to enhance BUC.

For the purpose,  
numerical simulation studies were performed.

- I. Introduction
- II. 3-D Nuclide Density Distribution**
- III. Total Neutron yield (Passive)
- IV. Source Multiplication
- V. Conclusion and Future Work

## FA of which nuclide densities are calculated

For the simulation study,  
3-D nuclide density distributions in **typical FA** are evaluated.

## Fuel & Core type and calculation codes

Fuel type	Burn-up (BU) (MWd/kgHM)	Core Type	Codes, assembly/core
PWR 17x17 UO <sub>2</sub>	Max < 55	3Loop 157FAs	AEGIS /SCOPE-2
PWR 17x17 UO <sub>2</sub> +Gd	Max < 55	3Loop 157FAs	AEGIS /SCOPE-2
BWR 9x9 UO <sub>2</sub> +Gd	Max = 55 Ave. = 45	ABWR 872FAs	TGBLA03 /LOGOS ver.5

## Calculation Scheme

- (1) Equilibrium core designing  
*typical history of*  
*power, void fraction(VR), moderator density, CR, etc.*  
 PWR: Full core calc. with pin-wised mesh (**SCOPE-2**)  
 BWR: Full core calc. (**LOGOS ver. 5**)
- (2) Selection of **typical FA**  
 PWR: FA of max. burn-up (BU)  
 BWR: FA of average BU and VR.
- (3) 2-D neutron transport & burn-up calc. for *assembly nodes*  
 (Divide the FA into 24 equal length, vertically)  
 PWR (**AEGIS**)  
 BWR (**TGBLA**)  
 → **3-D pin by pin nuclide densities** at the end of each cycle.  
**Calculations are supported by NFI, NEL, and GNF-J.**

## Nuclide List

Actinides	<sup>234</sup> U	<sup>235</sup> U	<sup>236</sup> U	<sup>238</sup> U	<sup>237</sup> Np
	<sup>238</sup> Pu	<sup>239</sup> Pu	<sup>240</sup> Pu	<sup>241</sup> Pu	<sup>242</sup> Pu
	<sup>241</sup> Am	<sup>242m</sup> Am	<sup>243</sup> Am		
	<sup>242</sup> Cm	<sup>243</sup> Cm	<sup>244</sup> Cm		
Fission Products	<sup>95</sup> Mo	<sup>99</sup> Tc	<sup>101</sup> Ru	<sup>106</sup> Ru	
	<sup>103</sup> Rh	<sup>106</sup> Rh	<sup>109</sup> Ag	<sup>131</sup> Xe	
	<sup>133</sup> Cs	<sup>134</sup> Cs	<sup>137</sup> Cs	<sup>144</sup> Ce	<sup>141</sup> Pr
	<sup>143</sup> Nd	<sup>145</sup> Nd	<sup>148</sup> Nd	<sup>147</sup> Pm	
	<sup>147</sup> Sm	<sup>149</sup> Sm	<sup>150</sup> Sm	<sup>151</sup> Sm	<sup>152</sup> Sm
	<sup>153</sup> Eu	<sup>154</sup> Eu	<sup>155</sup> Eu		
	<sup>154</sup> Gd	<sup>155</sup> Gd	<sup>156</sup> Gd	<sup>157</sup> Gd	<sup>158</sup> Gd

not evaluated for BWR  
not evaluated for PWR

In the following analysis,  
nuclide densities 10 years after discharged are used.

- I. Introduction
- II. 3-D Nuclide Density Distribution
- III. Total Neutron yield (Passive)**
- IV. Source Multiplication
- V. Conclusion and Future Work

## Total Neutron Yield and Neutron Leakage

Total neutron yield originated in actinide neutron source accumulated in FA is considered a good indicator of BU.

*Passive measurements had been performed conventionally*

### How to measure it without knowledge of BU?

- Total neutron yield = absorption inside FA  
+ absorption outside FA
- Horizontal buckling  $B_h^2$  of LWR FA is large  
= neutrons horizontally leak
- Neutron detection outside FA is easier than inside it


Ratio of absorption outside FA to total neutron yield  
= neutron leakage probability  $P_L$  is investigated.

## Fixed Source Calculation for Isolated FA

- Nuclide density for each pin divided into 24 segments
- Grid spacer, nozzle, tie-plate are neglected
- 50cm thick light water surrounds the FA
- Channel box for BWR.
- 300K, 1atm

**SOURCES4C** for spectra and yield from radioactive decay of actinides


**MCNP-5** for neutron multiplication & transport with ENDF/B-VI lib.



## Leakage Probability

$P_L$  of PWR FAs  
almost constant to BU.  
from 0 to 55 MWd/kgHM


$P_L$  of BWR FAs  
slightly increases with BU  
but max/min ratio < 1.042  
from 0 to 48 MWd/kgHM



In typical PWR and BWR FAs,  $P_L$ s are almost constant to BU.

## Mechanism of Constant $P_L$

- In FA,  $B_h^2 \gg B_z^2$  &  $B_h^2 > B_m^2$   
 $B_z^2$ : axial buckling  
 $B_m^2$ : material buckling
- FA  $\approx$  homogenous rectangular shape core.
- Putting a point source, neutron flux  
 $\rightarrow \exp(-\gamma z) \times \cos(B_h x) \times \cos(B_h y)$   
 $\gamma$ : spatial decay constant
- $P_L \approx DB_h^2 / (DB_h^2 + \Sigma_a)$   
 $D$ : diffusion constant,  $\Sigma_a$ : absorption cross section




Relations of  $\Sigma_a$  &  $D$  to BU are key issue of constant  $P_L$ .



## Macroscopic Cross Section

Calculation of  $\Sigma_a$  and its components for assembly node.




Nauchi, Kameyama, Sasahara, Central Research Institute of Electric Power Industry



## Diffusion Constant

D is approximated for each assembly node.

- Extension of assembly node
- Put a source.
- Fixed source calc. for  $\phi$  & J
  - $\phi$ : neutron flux
  - J: neutron current
- $J = -D (d\phi / dz) \phi$



D is almost constant to BU.

Constant  $\Sigma_a$  and D leads to constant  $P_L$ .

Nauchi, Kameyama, Sasahara, Central Research Institute of Electric Power Industry





## $P_L$ and Total Neutron Yield Measurements

Total neutron yield can be deduced by

Quantification of neutron absorption outside FA and  
constant  $P_L$ .

Calibration can be done at 0MWd/kgHM without reactor record.

Total neutron yield is available for BU confirmation.



## Quantification of Neutron Absorption Outside FA

~ Contents in this sheets had been published in Ann. Mtg. of AESJ (Mar. 2011)


Quantification of neutron absorption outside FA  
by counting the 2.2MeV  $\gamma$  ray.

No perturbation to neutron flux.

Independent to neutron spectrum

The 1<sup>st</sup> test had been  
performed in Kyoto Univ.  
Critical Assembly

Neutron absorption in water  
in ROI is measured within  
accuracy of 7%.



Quantification of neutrons outside FA is principally available.

The total neutron yield can be deduced with the constant  $P_L$ .



## $P_L$ and Total Neutron Yield Measurements

Total neutron yield can be deduced by

Quantification of neutron absorption outside FA and  
constant  $P_L$ .

Calibration can be done at 0MWd/kgHM without reactor record.

Total neutron yield is available for BU confirmation.



- I. Introduction
- II. 3-D Nuclide Density Distribution
- III. Total Neutron yield (Passive)
- IV. Source Multiplication**
- V. Conclusion and Future Work

## Subcriticality indices


There are several indices of burn-up reactivity depletion,

$k_{\text{sub}}$ : subcritical multiplication factor  
 $\gamma^2$ : axial buckling  
 $\alpha$ : prompt neutron decay constant


Among them,  $k_{\text{sub}}$  by the source multiplication method is most widely used in reactor experiments.

Utilizing the 3-D nuclide density distribution,  $k_{\text{sub}}$  is calculated for an isolated FA and compared to effective multiplication factor  $k_{\text{eff}}$  of *tight casks* which are filled with FAs of the same nuclide density.

PWR  
tight  
Cask  
21FA



BWR tight  
Cask  
45FA



## Source Multiplication in FA

Source condition:

PWR: all control rod guide tubes are filled with  $^{252}\text{Cf}$


BWR:  $^{252}\text{Cf}$  rod of 3.6m long is set 1cm outside channel box

BWR:

$k_{\text{sub}}$  can not be used for prediction of  $k_{\text{eff}}$  of tight cask.

PWR:

$k_{\text{sub}}$  for FA uniquely relates to  $k_{\text{eff}}$  of the tight cask.



## Source Multiplication and $P_L$ of PWR FA

$P_L$  for PWR  
( $UO_2$  &  $UO_2+Gd$ )  
in which  $^{252}Cf$  is inserted  
is calculated




$P_L$  varies little with BU.

= Total neutron yield &  $k_{sub}$

can be measured by quantification of neutron abs. outside FA.

Calibration (determining detector efficiency and  $^{252}Cf$  source strength) can be done with fresh FA. It does not require reactor record.



- I. Introduction
- II. 3-D Nuclide Density Distribution
- III. Total Neutron yield (Passive)
- IV. Subcriticality Measurement
- V. Conclusion and Future Work

## Conclusions

- 3-D nuclide density distributions in typical FA
- Numerical simulation of neutron transport in LWR FA
- $P_L$  of isolated FA in water is almost constant with BU both for accumulated actinide source and inserted  $^{252}\text{Cf}$  one.
- With the constant  $P_L$ , the total neutron yield can be deduced by measuring neutron absorption outside FA.  
Calibration can be done without reactor record.
- In passive measurements of PWR & BWR FA, total neutron yield certifies the Burn-up of the FA.
- In source-multiplication measurement of PWR FA, the total neutron yield provides  $k_{\text{sub}}$  which certifies reactivity depletion.

## Future Work

Demonstration of measurement of the total neutron yield utilizing the constant leakage probability  $P_L$  with the proposed  $\gamma$  ray measurement technique shall be done for commercial spent fuel assembly.

Thank you for your attention.



## Exponential Experiments

$\gamma^2$  of the middle height of FAs are approximately calculated and compared to effective multiplication factor  $k_{\text{eff}}$  of *tight* casks.

PWR  $\text{UO}_2$  FA:


$\gamma^2$  is good index of  $k_{\text{eff}}$

PWR  $\text{UO}_2 + \text{Gd}$  FA:

$\gamma^2$  can be index of  $k_{\text{eff}}$  of tight cask, but slope of  $k_{\text{eff}}$  vs  $\gamma^2$  changes when Gd is depleted

BWR FA:

$\gamma^2$  can not be index of  $k_{\text{eff}}$ .



The exponential experiments is more influenced by Gd contents than the source multiplication method.

## Eigenvalue of FA isolated in water

PWR-UO<sub>2</sub> without Gd

$k_{eff}$  monotonously decreases


PWR with Gd

BU- $k_{eff}$  swing is smaller than PWR-UO<sub>2</sub>

BWR

max.  $k_{eff}$  is at 1-cycle irradiated case

The trend depends on the amount of Gd.



Nauchi, Kameyama, Sasahara, Central Research Institute of Electric Power Industry




## Postulated transport casks

Postulated transport casks in which only well irradiated FAs can be loaded.

PWR: 21FAs

BWR: 45 FAs

Diameter of the casks are identical to conventional ones in which FAs of new fuel without Gd can be loaded



Nauchi, Kameyama, Sasahara, Central Research Institute of Electric Power Industry





## *Eigenvalue of Postulated Tight Casks in which FAs of the same nuclide densities are filled*

Discharge Cycle	PWR UO <sub>2</sub> , 21 FAs		PWR Gd, 21 FAs		BWR, 45 FAs	
	$k_{\text{eff}}$	error	$k_{\text{eff}}$	error	$k_{\text{eff}}$	error
0	1.3133	0.0002	1.0718	0.0003	0.8711	0.0002
1	1.1909	0.0003	1.0230	0.0003	1.0194	0.0003
2	1.0726	0.0003	1.0181	0.0003	0.9223	0.0003
3	0.9594	0.0003	0.9289	0.0003	0.8294	0.0002
4	0.8915	0.0003	0.8496	0.0002	0.7409	0.0002
5					0.7311	0.0002

We need to discriminate the FA of lower BU by  
measurements we will develop.